

Lip seal as pipe plug connection

Function:

These leak-tested and backflow-proof seals, which are compliant with the relevant standards for connecting two different pipe diameters, are ideally suited for use as a seal when connecting gullies to flat roof drains.

Material:

- EPDM, rubber Black
- UV- and ozone-resistant
- Good resistance to chemicals, temperature and tread load

Available sizes:

- D 50 mm (DN 50)
- D 75 mm (DN 70)
- D 95 mm small
- D 95 mm large
- D 110 mm (DN 100)
- D 125 mm (DN 125)
- D 160 mm (DN 150)

Packaging units:

Delivery in box / polybag, PU 1 piece



Technical data				
Lip seal	Size drain	Outer dimension seal	Matching with	Lip seal - backflow-proof area
Lip seal Ø D 50 mm (DN 50)	D 50 mm (DN 50)	73 x 29 mm	D 75 mm (DN 70)	61 to 77 mm
Lip seal Ø D 75 mm (DN 70)	D 75 mm (DN 70)	109 x 38 mm	D 110 mm (DN 100)	97 to 108 mm
Lip seal Ø D 95 mm small	D 95 mm	113 x 19 mm	D 110 mm (DN 100)	100 to 130 mm
Lip seal Ø D 95 mm large	D 95 mm	146 x 30 mm	D 125 mm (DN 125)	100 to 130 mm
Lip seal Ø D 110 mm (DN 100)	D 110 mm (DN 100)	126 x 35 mm	D 125 mm (DN 125)	120 to 135 mm
Lip seal Ø D 125 mm (DN 125)	D 125 mm (DN 125)	172 x 32 mm	D 160 mm (DN 150)	152 to 160 mm
Lip seal Ø D 160 mm (DN 150)	D 160 mm (DN 150)	207 x 33 mm	D 165 to D 180 mm	150 to 180 mm

KALA - KUNSTSTOFFE | Karl-Heinz Lange GmbH+Co.KG reserves the right to make technical changes.