

Lip seal for pipe connections

Function:

When connecting gullies to flat roof drains, these leak-tested, backflow-proof and compliant seals for connecting two different pipe diameters are ideal for sealing purposes.

Material:

- EPDM, rubber black
- UV and ozone resistant
- strong resilience to chemicals, temperature and footsteps

Available sizes:

- D 50 mm (DN 50)
 - D 75 mm (DN 70)
 - D 95 mm small
 - D 95 mm large
- D 110 mm (DN 100)
 - D 125 mm (DN 125)
 - D 160 mm (DN 150)

Package units:

Supplied in cartons / foil bags, PU 1 unit



Technical data			
Version lip seal	Size drains	External dimensions / height	Suitable for
D 50 mm (DN 50)	D 50 mm (DN 50)	73 x 29 mm	D 75 mm (DN 70)
D 75 mm (DN 70)	D 75 mm (DN 70)	109 x 38 mm	D 110 mm (DN 100)
D 95 mm small	D 95 mm	113 x 19 mm	D 110 mm (DN 100)
D 95 mm large	D 95 mm	146 x 30 mm	D 125 mm (DN 125)
D 110 mm (DN 100)	D 110 mm (DN 100)	126 x 35 mm	D 125 mm (DN 125)
D 125 mm (DN 125)	D 125 mm (DN 125)	172 x 32 mm	D 160 mm (DN 150)
D 160 mm (DN 150)	D 150 mm (DN 150)	207 x 33 mm	D 165 mm up to D 180 mm

KALA – KUNSTSTOFFE | Karl-Heinz Lange GmbH+Co.KG reserves the right to make technical changes.